

Specifications

Product type			Meter
Meter type			Combo
Brand			SIGNAL
Model			ST-5155
Measured parameters			Signal power level, MER, BER, C/N
Monitoring of channels			Yes
	Display	p	800 × 480
	video decoding supported		HEVC, MPEG-2, MPEG-4/H.264, H.265
	audio decoding supported		Dolby AC3/AC3+, MPEG-1/2 Layer I/II/III
Specifications			
Receiver DVB-T/T2/C	Frequency range	MHz	48...862
Receiver DVB-T/T2/C	Signal strength	dBμV	> 30 (DVB-T/T2), > 42 (DVB-C)
	Antenna supply	V	5, 12
	Modulation		QPSK, 16QAM, 64QAM, 256QAM
	Connector		F-socket
Receiver DVB-S/S2	Frequency range	MHz	950...2150
Receiver DVB-S/S2	Signal strength	dBμV	44...85
	converters supported		Fullband, Unicable (dCSS), Unicable (dSCR), Wideband
	DISEqC		Yes – 1.0, 1.1
	LNB supply	V	13/18 (max. 350 mA)
	Modulation		QPSK, 8PSK, 16APSK, 32APSK
	Connector		F-socket
Power supply			
Power consumption		W	max 10
Battery	type		Li-Ion 7.4 V
Battery	capacity	mAh	2600
Other information			
Additional connectors			A/V, HDMI, USB
Accessories			wall charger
Dimensions		mm	170 × 120 × 40
Weight		kg	1